

Selection guide

This is only provided as a GUIDE. Combined distances may be exceeded in many cases. However, customers need to evaluate suitability for each situation.

Code	Use	Indoor Outdoor	Max Comb. Distance*	Size (mm)	Mirror Face	Wall	Fixture Ceiling	Pole	Back
DuraVision Standard Range									
Standard Acrylic									
18020J	All Indoor Situations	I	5m	300	Acrylic	✓	✓		Hardboard
18038J		I	7m	450	Acrylic	✓	✓		Hardboard
18056J		I	10m	600	Acrylic	✓	✓		Hardboard
18072J		I	13m	760	Acrylic	✓	✓		Hardboard
18108J		I	18m	900	Acrylic	✓	✓		Plywood
18112J		I	over 18m	1200	Acrylic	✓	✓		Plywood

DuraVision Wide Area Domes

Ceiling Domes

18585H	Open Areas	I	6m	600	Acrylic		✓		n/a
18590H	(360° Vision)	I	9m	900	Acrylic		✓		n/a
18596H		I	over 9m	1200	Acrylic		✓		n/a

Half Domes

18535H	Walls &	I	6m	600 x 300	Acrylic	✓			n/a
18553H	Adjacent Areas	I	9m	900 x 450	Acrylic	✓			n/a
18556H	(180° Vision)	I	over 9m	1200 x 600	Acrylic	✓			n/a

Quarter Domes

18541H	Corner	I	3m	300 x 300	Acrylic	✓			n/a
18560H	Areas	I	6m	450 x 450	Acrylic	✓			n/a
18563H	(90° Vision)	I	over 6m	600 x 600	Acrylic	✓			n/a

DuraVision Heavy Duty Range

Impact Resistant

18026S	Industrial	I/O	21m	300	Acrylic	✓		✓*	Plywood
18044S	Indoor	I/O	28m	450	Acrylic	✓		✓*	Plywood
18062S	& Normal	I/O	38m	600	Acrylic	✓		✓*	Plywood
18078S	Outdoor	I/O	46m	760	Acrylic	✓		✓*	Plywood
18114S	Conditions	I/O	55m	900	Acrylic	✓		✓*	Plywood
18118S		I/O	over 55m	1200	Acrylic	✓		✓*	Plywood

Unbreakable

16062S	High Risk	I/O	42m	600	S/Steel	✓		✓*	Plywood
16087S	Industrial	I/O	60m	800	S/Steel	✓		✓*	Plywood
16445S	Conditions	I/O	over 60m	1000	S/Steel	✓		✓*	Plywood

DuraVision De Luxe Range

Impact Resistant

18066J	Normal to	O	38m	600	Acrylic	✓		✓	Steel
18087J	Extreme	O	50m	800	Acrylic	✓		✓	Steel
18445J	Conditions	O	over 50m	1000	Acrylic	✓		✓	Steel

Unbreakable

16029J	Extreme Industrial Conditions	O	23m	300	S/Steel	✓		✓	Steel
16047J		O	32m	450	S/Steel	✓		✓	Steel
16066J		O	42m	600	S/Steel	✓		✓	Steel
16087J		O	60m	800	S/Steel	✓		✓	Steel
16445J		O	over 60m	1000	S/Steel	✓		✓	Steel

DuraVision Rear Vision Range

Impact Resistant

18026S		I/O	21m	300	Acrylic	✓	✓	✓*	Plywood
--------	--	-----	-----	-----	---------	---	---	----	---------

Unbreakable

16336C		I/O	13m	225 x 320	S/Steel	✓	✓	✓	Steel
--------	--	-----	-----	-----------	---------	---	---	---	-------

♦ = The combined distance is the distance from the observer to the mirror PLUS the distance from the mirror to the object being observed.

* = U-bolt accessory pack not included, optional extra.

User shall determine the suitability of the product for their intended use and assume all risk and liability in connection therewith.