

Selection guide

This is only provided as a GUIDE. Combined distances may be exceeded in many cases. However, customers need to evaluate suitability for each situation.

Code	Use	Indoor Outdoor	Max Comb. Distance †	Size (mm)	Mirror Face	Wall	Fixture Ceiling	Pole	Back
------	-----	-------------------	-------------------------	-----------	----------------	------	--------------------	------	------

DuraVision Standard Range

Standard Acrylic

18020J	All Indoor Situations	I	5m	300	Acrylic	✓	✓		Hardboard
18038J		I	7m	450	Acrylic	✓	✓		Hardboard
18056J		I	10m	600	Acrylic	✓	✓		Hardboard
18072J		I	13m	760	Acrylic	✓	✓		Hardboard
18108J		I	18m	900	Acrylic	✓	✓		Plywood
18112J		I	over 18m	1200	Acrylic	✓	✓		Plywood

Space Saver Mirrors

18330A	Confined	I	10m	600 x 400	Acrylic	✓	✓		n/a
18332A	Indoor Areas	I	over 10m	800 x 600	Acrylic	✓	✓		n/a

DuraVision Wide Area Dome Range

Wide Area Dome Mirrors

18585H	Open Areas (360° Vision)	I	6m	600	Acrylic		✓		n/a
18590H		I	9m	900	Acrylic		✓		n/a
18596H		I	over 9m	1200	Acrylic		✓		n/a

T-Junction Half Dome Mirrors

18535H	Walls & Adjacent Areas (180° Vision)	I	6m	600 x 300	Acrylic	✓			n/a
18553H		I	9m	900 x 450	Acrylic	✓			n/a
18556H		I	over 9m	1200 x 600	Acrylic	✓			n/a

Corner Quarter Dome Mirrors

18541H	Corner Areas (90° Vision)	I	3m	300 x 300	Acrylic	✓			n/a
18560H		I	6m	450 x 450	Acrylic	✓			n/a
18563H		I	over 6m	600 x 600	Acrylic	✓			n/a

DuraVision Heavy Duty Range

Impact Resistant

18026S	Industrial & Normal Outdoor Conditions	I / O	21m	300	Acrylic	✓		✓*	Plywood
18044S		I / O	28m	450	Acrylic	✓		✓*	Plywood
18062S		I / O	38m	600	Acrylic	✓		✓*	Plywood
18078S		I / O	46m	760	Acrylic	✓		✓*	Plywood
18114S		I / O	55m	900	Acrylic	✓		✓*	Plywood
18118S		I / O	over 55m	1200	Acrylic	✓		✓*	Plywood

Unbreakable

16062S	High Risk Industrial Conditions	I / O	42m	600	S/Steel	✓		✓*	Plywood
16087S		I / O	60m	800	S/Steel	✓		✓*	Plywood
16445S		I / O	over 60m	1000	S/Steel	✓		✓*	Plywood

DuraVision De Luxe Range

Impact Resistant

18066J	Normal to Extreme Conditions	O	38m	600	Acrylic	✓		✓	Steel
18087J		O	50m	800	Acrylic	✓		✓	Steel
18445J		O	over 50m	1000	Acrylic	✓		✓	Steel

Unbreakable

16029J	Extreme Industrial Conditions	O	23m	300	S/Steel	✓		✓	Steel
16047J		O	32m	450	S/Steel	✓		✓	Steel
16066J		O	42m	600	S/Steel	✓		✓	Steel
16087J		O	60m	800	S/Steel	✓		✓	Steel
16445J		O	over 60m	1000	S/Steel	✓		✓	Steel

♦ = The combined distance is the distance from the observer to the mirror PLUS the distance from the mirror to the object being observed.

* = U-bolt accessory pack not included, optional extra.

User shall determine the suitability of the product for their intended use and assume all risk and liability in connection therewith.