



# DuraVision™ Traffic

## Selection guide

*This is only provided as a GUIDE. Combined distances may be exceeded in many cases. However, customers need to evaluate suitability for each situation.*

Range	Code	Recommended Uses		Max Comb. Distance <sup>◆</sup>	Size (mm)	Mirror Face	Bracket		Back
		Weather Conditions	Vandalism Conditions				J	Post Clamp	
<b>Low Speed Traffic (&lt;50km/h)</b>									
<b>Impact Resistant - Rectangular</b>									
Pro Series	18642R	Normal	Normal	38m	400 x 600	Acrylic		✓	ASA
Pro Series	18645R	Normal	Normal	50m	600 x 800	Acrylic		✓	ASA
Pro Series	18648R	Normal	Normal	over 50m	800 x 1000	Acrylic		✓	ASA
<b>Impact Resistant - Circular</b>									
Pro Series	18666C	Normal	Normal	38m	600	Acrylic		✓	ASA
Pro Series	18687C	Normal	Normal	50m	800	Acrylic		✓	ASA
Pro Series	18695C	Normal	Normal	over 50m	1000	Acrylic		✓	ASA
Heavy Duty	18062S	Normal	Normal	38m	600	Acrylic	✓*		PVC
Heavy Duty	18078S	Normal	Normal	46m	760	Acrylic	✓*		PVC
Heavy Duty	18114S	Normal	Normal	55m	900	Acrylic	✓*		PVC
Heavy Duty	18118S	Normal	Normal	over 55m	1200	Acrylic	✓*		PVC
De Luxe	18066J	Extreme	Normal	38m	600	Acrylic	✓		Steel
De Luxe	18087J	Extreme	Normal	50m	800	Acrylic	✓		Steel
De Luxe	18445J	Extreme	Normal	over 50m	1000	Acrylic	✓		Steel
<b>Unbreakable</b>									
Heavy Duty	16062S	Extreme	Extreme	42m	600	Stainless	✓*		PVC
Heavy Duty	16087S	Extreme	Extreme	60m	800	Stainless	✓*		PVC
Heavy Duty	16445S	Extreme	Extreme	over 60m	1000	Stainless	✓*		PVC
De Luxe	16066J	Extreme	Extreme	42m	600	Stainless	✓		Steel
De Luxe	16087J	Extreme	Extreme	60m	800	Stainless	✓		Steel
De Luxe	16445J	Extreme	Extreme	over 60m	1000	Stainless	✓		Steel
<b>High Speed Traffic (&gt;50km/h)</b>									
<b>Impact Resistant - Rectangular</b>									
Pro Series	18645R	Normal	Normal	42m	600 x 800	Acrylic		✓	ASA
Pro Series	18648R	Normal	Normal	over 42	800 x 1000	Acrylic		✓	ASA
<b>Impact Resistant - Circular</b>									
Pro Series	18666C	Normal	Normal	32m	600	Acrylic		✓	ASA
Pro Series	18687C	Normal	Normal	42m	800	Acrylic		✓	ASA
Pro Series	18695C	Normal	Normal	over 42m	1000	Acrylic		✓	ASA
De Luxe	18066J	Extreme	Normal	32m	600	Acrylic	✓		Steel
De Luxe	18087J	Extreme	Normal	42m	800	Acrylic	✓		Steel
De Luxe	18445J	Extreme	Normal	over 42m	1000	Acrylic	✓		Steel
<b>Unbreakable</b>									
Heavy Duty	16062S	Extreme	Extreme	36m	600	Stainless	✓*		PVC
Heavy Duty	16087S	Extreme	Extreme	58m	800	Stainless	✓*		PVC
Heavy Duty	16445S	Extreme	Extreme	over 58m	1000	Stainless	✓*		PVC
De Luxe	16066J	Extreme	Extreme	36m	600	Stainless	✓		Steel
De Luxe	16087J	Extreme	Extreme	58m	800	Stainless	✓		Steel
De Luxe	16445J	Extreme	Extreme	over 58m	1000	Stainless	✓		Steel

- ◆ = The combined distance is the distance from the observer to the mirror PLUS the distance from the mirror to the traffic being observed.
- \* = U-bolt accessory pack not included, optional extra.

User shall determine the suitability of the product for their intended use and assume all risk and liability in connection therewith.

In keeping with constant improvement policies, the manufacturer reserves the right to alter products or specifications without notice.